Gearbox Repair Experiences

2006 Wind Turbine Reliability Workshop

Thomas Jonsson, Business Manager
Moventas Inc.

What happens if units run too long?

moventas

Tooling for disassembly

moventas

Failure Types in Wind Turbine Gearboxes (500-900 kW)





moventas

What can be done to prevent it?

- Root Cause Identification and Analysis
- Example: 3 point WTG 1.5 MW
  - Radial movement 0.5 mm
  - By Allianz Zentrum for Technik

moventas

How failures are detected today?

Component observed	Typical Failure	Primary Signal	Detection
Oil Pump	**wear/dammage**	Low oil pressure	direct
High Speed Bearings	**failure**	High Temp - PT 100	direct
IM Bearing	**failure**	Metal in sump	@ service
IM Pinion	**tooth failure**	Vibration	@ service
LS Pinion	**tooth failure**	Vibration	@ service
Planet Wheel	**tooth failure**	Vibration	@ service
Planet Bearing	**failure**	Metal un sump	@ service
Planet Gear	**tooth failure**	Vibration	@ service
Torque Arm	**cracks**	Visual	@ service

moventas

What has changed in 10 years

- Gearbox Design and Calculation programs
  - Grade of sophistication has increased
- Simulations
  - Load definitions have improved
- Accelerated LC tests
  - Requirement for MW units has been introduced
- WTG Software modifications
  - Softer regulated programs (Ramp up – ramp down)
- Condition monitoring
  - Tools for MW being implemented

moventas

Condition Management

Features

- Flexible interface may be modified for customer needs
- Intelligent data reduction, classification and analysis
- Providing on line monitoring and analysis services

moventas

Condition Management

Methods for early warning and condition monitoring

- **Root cause for wear and failure processes**
  - Lubrication film is insufficient
    - Too high temperature
    - Particles or dirty in the oil
    - Lack of additives
  - Wear and further surface fatigue particles are developed
  - Vibration level is increased
  - Failure
- **Key factors in a gear unit lifetime**
  - Good lubricating system with good lubricant
  - Good lubricant chemical condition
  - Loading conditions equates the specified loading spectrum
  - Early warning of the changed working (loads, speed, lubrication) conditions

moventas

Condition Management

Method of early warning



moventas

Condition Management

Features



- Trend of oil properties; good operating conditions guarantee longer lifetime for bearings and gears
- Trend of wear particles; early signal of any wear
- Torque measurements; knowledge of real load conditions, power spectra and detection of harmful operating conditions
- Local measurement of bearing and oil temperatures; early signal of cooling system malfunction or lubrication problems
- Measuring vibration of components; failure detection, early signal of misalignment

moventas

Condition Management

Benefits

- Continuous 24h monitoring
- Cost savings; higher availability and lower maintenance costs
- Early signal of failure
- Planned maintenance instead of unexpected failure and costs
- Longer lifetime by knowledge of real loads, avoiding harmful operations
- Condition analysis and support

moventas

Condition Management

Condition Management and self diagnostics system



moventas